



*****Slewing Ring mount to left of input, ring not included*****

PART #	A	B	C	D	E	F	G	H	I	J	K	L	M
SD5300C	10.43	1.59	5.345	1.03	1.266	2.959	4.59	8	0.62	0.5		Ø4.00	Ø9.402
SD6900C	14.125	2.719	6.978	1.063	2.063	3.94	6.25	12.24	0.75	0.88	R6.36	Ø5.375	Ø8.875
SD9300C	18.813	2.719	9.354	1.188	2	3.875 MAX	6.81	13.5	0.75	0.88	R8.75 0	Ø10.00	Ø13.50
SD1100C			11.135	1.203		MAX	7.88	15.32	0.75	0.88		1	Ø16.688

PART #	N	O	P	Q	R	S	T
SD5300C	(10) Ø.437 THRU EQUALLY SPACED ON 4.750 B.C.		(3) .281 HOLES ON A 1.772 B.C. C'BORE ON BACK FOR 1/4-28UNF CAP SCREWS	MOTOR ADAPTER FOR CHAR LYNN "J-2"(M) SERIES HYDRAULIC MOTOR 31.5mm PILOT .625" SHAFT WITH 3/16" KEYWAY			73:1
SD6900C	(16) Ø.714"/.739" HOLES EQUALLY SPACED ON 6.890" B.C.	(4) Ø.344" HOLES THRU C'BORE Ø.698" x .38" DEEP FAR SIDE ON 6.890" B.C.	(2) DRILL Ø.313" x 1.375" DEEP TAP 3/8-16NC x 1.125" DEEP ON 4.187 B.C.	MOTOR MOUNT FOR STD SAE "A" 1.0005/1.0020 BORE .250/.252 KEYWAY 3.251/3.253 C'BORE	RIGHT	SINGLE	61:1
SD9300C	(24) Ø.714"/.739" THRU EQUALLY SPACED ON 11.614" B.C.	(4) Ø.375" THRU C'BORE Ø.813" x .43" DEEP BACK SIDE ON 11.614" B.C. STEEL WASHER	(2) 12-13NC x 1.125" DEEP ON 4.187 B.C.	MOTOR MOUNT FOR STD SAE "A" 1.0005/1.0020 BORE .250/.252 KEYWAY 3.251/3.253 C'BORE	RIGHT	SINGLE	85:1
SD1100C	(20) Ø.719"/.739" HOLES THRU HOUSING EQUALLY SPACED ON 14.375" B.C.	(4) Ø.375" THRU C'BORE Ø.812" x .438" DEEP EQUALLY SPACED ON 14.375" B.C.	(2) 1/2-13NC x 1.00" DEEP ON 4.187" B.C.	MOTOR ADAPTER & MOUNTING HOLES TO FIT SAE "A" TYPE 2-BOLT STD HYDRAULIC MOTOR W/Ø25mm SHAFT & 8mm	RIGHT	SINGLE	103:1